HD Analog Day/ Night Fixed IR Dome Camera

CV-CFN103L

1280 (H) x 720 (V) 0.05Lux/ F1.6, 0Lux IR on

1/50s~1/100,000s

Auto (ICR)/ Color/ B/W

25fps

20m

Auto

Auto

Auto

M12

3.6 mm

H: 88° V: 46°

DC 12V±25%

-30°C~+60°C

Φ85 mm × 69 mm

Wall mount/ In-ceiling mount

2.2W MAX

100g

Plastic

1 CH BNC HD-CVI video output

Less than 95% RH (no condensation)

2D

Internal

1/2.9" 1.0 Mega Pixels CMOS

Panasonic

CV-CFN103L CV-CFN103LN

CV-CFN103LN

1/60s~1/100,000s

30fps

Smart look Indoor Day/ Night Fixed Dome Camera with IR illuminator




Key Features


- High-performance CMOS image sensor.
- Support 720p@25fps (PAL)/ 30fps (NTSC)
- Support 75-3 coaxial cable transmission over 800m.
- High speed & long distance real-time transmission.
- Support ICR for day time and night time operation.
- Support auto exposure, auto white balance, auto electronic shutter and auto gain function.
- Support DC12V power supply.

Standard Accessories

- Quick guide.....1 pc
- Important safety instruction.....1 pc

Appearance





Important

- Safety Precaution: Carefully read the operating instruction manual before using this product.

- All pictures are simulated.
- Weights and dimensions are approximate.
- Specifications are subject to change without notice.

These products may be subject to export control regulations.

DISTRIBUTED BY: JIA YING TRADING PTE LTD 1 Rochor Canal Road #02-67 Sim Lim Square Singapore 188504 Tel: 63360404 Fax: 63380404 Website: www.jiaying.com

Specifications

Camera

Image Sensor Effective Pixels

Min Illumination **Electronic Shutter**

Video Frame Rate

Digital Noise Reduction

Synchronization

Day & Night Max IR Distance

White Balance

Focal Length

Input / Output

Video Output

Dimensions

Weight (approx.)

Installation Mode

External Case

Lens Type

General

Power

Angular Field of View

Power Consumption

Working Temperature

AGC

BLC

Lens

Parameter

Email: jiaying@singnet.com.sg